FLEXI

TECHNICAL DATA SHEET

DIVERSITECH

INSTALL

FLEXI FOOT WITH STRUT KITS



Flexi Foot with Strut Kits – These kits can support air source heat pumps, and be used in single form as a flexi foot with strut on a variety of outdoor equipment such as cable trays and pipework etc.

FEATURES

- Kits available in three sizes: 400mm, 600mm and 1000mm
- Made from heavy-duty recycled rubber
- 21 x 41mm galvanized steel strut is supplied bonded to the rubber
- Drain slots molded to the underside of the foot

RELATED PRODUCTS

- Flexi Frames
- Flexi Lite Slab & Foot Kit
- Collection trays
- Floor mounting brackets
- ASHP soakaway
- Fix Clamp

THE PACKAGE

- 2 x Flexi Foot with Strut
- Bag of fixings
- Single foot options available in four sizes: 250mm, 400mm, 600mm and 1000mm

Material					
Rubber	Compression using milled, sieved and graded recycled rubber bound with high quality adhesive				
Density	1.0 kg/cm ³				
Strut	41 x 21 x 1.5mm galvanised steel				

Part code	Description	Length	Width	Height	Safe working load*	Weight
FF-400-S-KIT	2 x Flexi Foot 400mm - with fixings	400mm	185mm	100mm	400kg	9.2kg
FF-600-S-KIT	2 x Flexi Foot 600mm - with fixings	600mm	185mm	100mm	840kg	15.2kg
FF-1000-S-KIT	2 x Flexi Foot 1000mm - with fixings	1000mm	185mm	100mm	1400kg	24kg
FF-600-S-KIT-3	3 x Flexi Foot 600mm - with fixings	600mm	185mm	100mm	-	-
FF-600-S-150-KIT	2 x Flexi Foot 600mm - with fixings	600mm	130mm	150mm	-	-
FF-600-S-150-KIT-3	3 x Flexi Foot 600mm - with fixings	600mm	130mm	150mm	-	-

FLEXI FLEXI FOOT WITH STRUT KITS

The DiversiTech International sales team are available to answer your questions or queries on this product. Our experts are waiting for your call +44 (0)115 900 5858 or if you prefer send an email to sales@diversitech.com or visit www.diversitech.global



Glaisdale Drive East Nottingham NG8 4LY United Kingdom