## LEAK DETECTION



## TIF ZX-1A



This is the most sensitive and most advanced completely digital hand held leak detector available today. The ZX-1A eliminates false alarms from moisture, cleaners and solvents and allows you to home into even the smallest refrigerant leak without misleading feedback. Reliability is a key feature of the ZX-1A - the unit is equipped with a sensor failure indicator, a battery test function giving true voltage indication and a low battery indicator.

- Detects ALL halogenated refrigerants
- Suitable for A2L refrigerants such as R32 and R1234YF
- Wall charger included
- Rechargeable
- Mute Button
- Patented heated pentode sensor
- · Highest sensitivity in the market less than 3g/year
- True mechanical pump provides instant response
- Tri-colour leak size indication display
- 2-year warranty

Technical information	
Ultimate sensitivity	Less than 3 gr/yr for all refrigerants
Power supply	Ni-MH Battery Pack
Battery life	5-6 hours
Sensor life	100-150 hours
Operating temperature	0 to 50°C (32 to 122°F)

Part code	Description	Quantity
TIF ZX-1A	Heated Pentode™ Refrigerant Leak Detector	1
TIF ZX-2	Heated Pentode™ Sensor for ZX-1A	1
TIF ZX-14	Filter & Tip for ZX-1A	1
TIF ZX-20	Nickle-Metal Hydride (NiMH) Battery Pack for ZX-1A	1