SPEEDIDUCT

TECHNICAL DATA SHEET








SPEEDIDUCT EXTERNAL TRUNKING

- Easy to install, fittings with screws
- Protects the linesets and the unit
- Helps saving energy
- Extends the units life cycle
- Aesthetic Design
- Paintable
- UV-Resistant



- Made of rigid, shockproof, UVstabilised fire resistant PVC B
- High-quality (usable from -20°C / -4°F
 - +60°C / 140°F in a static position)
- Inside fixation rail (SpinFix) enables use cable ties to strap and keep the linesets in place - contributing to the duct rigidity



150 X 80MM

PRODUCT FEATURES AND BENEFITS

| 1 man job | Use the SpinFix-clip to keep ducts contents strapped while installing the cover. Easy and Fast! | |
|-----------------------------|--|--|
| Up to 150mm wide | Duct size 150 is the widest of its kind, ideal for multi-split or heat pump installations. It has 2 SpinFix rails: 1 in the top and 1 in the base channel. | |
| Rigid installation | Top-Bottom fittings assembled with stainless steel screws ensure a rigid installation. | |
| Large selection of fittings | Not all installations are the same. Some require specific fittings like the soffit inlet, the long flat bend with its larger bending radius for linesets. | |

TRUNKING AIR SOURCE HEAT PUMPS

EXTERNAL ISOMM TRUNKING

this product. Our experts are waiting for your call +44 (0)115 900 5858 or if you prefer send an email to sales@diversitech.com or visit www.diversitech.global



Glaisdale Drive East Nottingham NG8 4LY United Kingdom

TECHNICAL DATA SHEET



SPEEDIDUCT EXTERNAL TRUNKING





- Made of rigid, shockproof, UV-stabilised fire resistant PVC B
- High-quality (usable from -20°C / -4°F to +60°C / 140°F in a static position)
- Inside fixation rail (SpinFix) enables use of cable ties to strap and keep the linesets in place contributing to the duct rigidity



DUCT





| Description | Width | Colour | Part code |
|-------------------------------------|-------|--------|------------|
| SpeediDuct trunking (2000mm length) | 150mm | Black | TR-D-150-B |
| SpeediDuct trunking (2000mm length) | 150mm | White | TR-D-150-W |



CONNECTION PIECE





| Description | Width | Colour | Part code |
|-----------------------------|-------|--------|-------------|
| SpeediDuct Connection piece | 150mm | Black | TR-CP-150-B |
| SpeediDuct Connection piece | 150mm | White | TR-CP-150-W |



FLAT BEND





| Description | Width | Colour | Part code |
|----------------------|-------|--------|-------------|
| SpeediDuct flat bend | 150mm | Black | TR-FB-150-B |
| SpeediDuct flat bend | 150mm | White | TR-FB-150-W |



TRUNKING AIR SOURCE HEAT PUMPS

EXTERNAL ISOMM TRUNKING

this product. Our experts are waiting for your call +44 (0)115 900 5858 or if you prefer send an email to sales@diversitech.com or visit www.diversitech.global



Glaisdale Drive East Nottingham NG8 4LY United Kingdom

TECHNICAL DATA SHEET







■ SPEEDIDUCT EXTERNAL TRUNKING

WALL COVER





| Description | Width | Colour | Part code |
|-----------------------|-------|--------|-------------|
| SpeediDuct wall cover | 150mm | Black | TR-WC-150-B |
| SpeediDuct wall cover | 150mm | White | TR-WC-150-W |



90° EXTERNAL BEND





| Description | Width | Colour | Part code |
|------------------------------|-------|--------|-------------|
| SpeediDuct 90° external bend | 150mm | Black | TR-EC-150-B |
| SpeediDuct 90° external bend | 150mm | White | TR-EC-150-W |

■ 90° INTERNAL BEND





| Description | Width | Colour | Part code |
|------------------------------|-------|--------|-------------|
| SpeediDuct 90° internal bend | 150mm | Black | TR-IC-150-B |
| SpeediDuct 90° internal bend | 150mm | White | TR-IC-150-W |

TRUNKING AIR SOURCE HEAT PUMPS

EXTERNAL ISOMM TRUNKING

The DiversiTech International sales team are available to answer your questions or queries on this product. Our experts are waiting for your call +44 (0)115 900 5858 or if you prefer send an email to sales@diversitech.com or visit www.diversitech.global



Glaisdale Drive East Nottingham NG8 4LY United Kingdom