CANTILEVER ARMS TECHNICAL DATA SHEET



CANTILEVER ARMS





These ready-made, hot-dipped galvanised steel cantilever arms with 14mm diameter holes, offer a quick and easy method of supporting condensing units on external walls. Available in a straight length and webbed version in a variety of lengths. The strut dimensions are 41mm x 41mm x 2.5mm.

FEATURES

- Low cost mounting option
- Available in single, double and webbed versions
- Strut dimensions are 41mm x 41mm x 2.5mm
- Hot Dip Galvanised

THE PACKAGE

- Sold as singles
- 2 x cantilever arms for the kit webbed / single or double

RELATED PRODUCTS

- End Caps
- Fixings
- Drip Trays
- Cantilever Arm Kits

Part code	Description	Safe working load*	Length	Weight
CA-150-S	Cantilever arm – Single 150mm	250kg	150mm	0.8kg
CA-300-S	Cantilever arm – Single 300mm	250kg	300mm	1kg
CA-450-S	Cantilever arm – Single 450mm	250kg	450mm	1.4kg
CA-600-S	Cantilever arm – Single 600mm	190kg	600mm	2kg
CA-750-S	Cantilever arm – Single 750mm	150kg	750mm	2.4kg
CA-900-S	Cantilever arm – Single 900mm	120kg	900mm	3kg
		·		
CA-600-W	Cantilever arm – Webbed 600mm	190kg	600mm	2.6kg
CA-750-W	Cantilever arm – Webbed 750mm	150kg	750mm	3kg
CA-950-W	Cantilever arm – Webbed 950mm	150kg	950mm	3kg
CA-1200-W	Cantilever arm – Webbed 1200mm	150kg	1200 mm	3kg
CA-600-D	Cantilever arm – Double 600mm	243kg	600mm	3.7kg
CA-750-D	Cantilever arm – Double750mm	205kg	750mm	4.5kg
CA-900-D	Cantilever arm – Double 900mm	140kg	900mm	5.6kg
CA-1200-D	Cantilever arm – Double 1200mm	140kg	1200mm	5.6kg

The safe working loads quoted are for a concentrated load located at the mid-point of the arm.

SUPPORT CANTILEVER ARMS



^{*} It is the installer's responsibility to ensure that equipment weights do not exceed the safe working loads quoted