


3 CFM      5 CFM      8 CFM  
**■ RA1530-A3 | RA1550-A3 | RA1580-A3**  
**HIGH PERFORMANCE VACUUM PUMPS**

**ROBINAIR** **TOOLS+**



The new A3 VacuMaster high performance vacuum pumps from Robinair - the quality and trusted name in vacuum pumps for over 70 years.



## ■ FEATURES

- Spark proof components independently tested and validated against applicable sections of ANSI 12.12.01 standard
- For use on Class A1, A2, A2L or A3 refrigerant systems
- Dual voltage, dual frequency motor for use on 120 V or 230 V, 50/60 Hz power supplies
- 2 stage design to achieve lower ultimate vacuum, as low as 15 microns
- Gas ballast valve for deeper vacuum
- Dual inlet ports (1/4" MFL and 3/8" MFL)
- Rubber lined handle, skid resistant rubber base
- Optional Exhaust Venting Kit (RA1500-A3) for use when evacuating systems running with flammable refrigerants
- One Year Warranty



LOCKING POWER CORD CONNECTION PREVENTS ACCIDENTAL DISCONNECTION OF CORD WHICH COULD CREATE A HAZARD. ONE OF SEVERAL SMALL BUT CRITICAL SAFETY FEATURES OF OUR DESIGN. **(1)** DUAL VOLTAGE AND DUAL FREQUENCY POWER SUPPLY ENSURES TRUE GLOBAL COMPATIBILITY IN ONE PRODUCT. **(2)** GAS BALLAST ENABLES FASTER ACHIEVEMENT OF HIGH ULTIMATE VACUUM LEVEL. **(3)** SEALED AND SPARK FREE COMPONENTS MEET APPLICABLE REQUIREMENTS TO ENSURE SAFE OPERATION ON A2/L AND A3 SYSTEMS. **(2)**

**TOOLS**  
**RA1530-A3 | RA1550-A3 | RA1580-A3**  
 HIGH PERFORMANCE VACUUM PUMPS

The DiversiTech International sales team are available to answer your questions or queries on this product. Our experts are waiting for your call +44 (0)115 900 5858 or if you prefer send an email to [sales@diversitech.com](mailto:sales@diversitech.com) or visit [www.diversitech.global](http://www.diversitech.global)




**DIVERSiTECH**  
INTERNATIONAL

Glaisdale Drive East  
 Nottingham NG8 4LY  
 United Kingdom

3 CFM 5 CFM 8 CFM  
**RA1530-A3 | RA1550-A3 | RA1580-A3**  
 HIGH PERFORMANCE VACUUM PUMPS



## SPECIFICATIONS

	RA1530-A3 	RA1550-A3 	RA1580-A3 
MAXIMUM CURRENT	115 V 50/60 Hz – 5,84 A 230 V 50/60 Hz – 2,84 A	115 V 50/60 Hz – 6,26 A 230 V 50/60 Hz – 3,2 A	115 V 50/60 Hz – 9,87 A 230 V 50/60 Hz – 4,75A
FREE AIR DISPLACEMENT	3 cfm (85 l/m) @60 Hz 2.5 cfm (71 l/m) @50Hz	5 cfm (142 l/m) @60 Hz 4.1 cfm (116 l/m)@50Hz	8 cfm (227 l/m) @60 Hz 6.6 cfm (187 l/m) @50Hz
ULTIMATE VACUUM	15 microns (2 Pa)	15 microns (2 Pa)	15 microns (2 Pa)
STAGES	2	2	2
MOTOR	300 watt	350 watt	660 watt
INTAKE PORTS	1/4" & 3/8" Flare	1/4" & 3/8" Flare	1/4" & 3/8" Flare
OIL CAPACITY	560ml	480ml	610ml
DIMENSIONS	348 x 140 x 272mm	348 x 140 x 272mm	382 x 160 x 285mm
WEIGHT	10.2kg	11.2kg	15.2kg

## RELATED PRODUCTS



### RA1500-A3 EXHAUST VENTING KIT

Designed specifically for use with Robinair VacuMaster pumps this exhaust kit allows for the routing of evacuated gases to a safe area when servicing systems that use flammable refrigerants. Length: 10 meters.



**TOOLS**  
**RA1530-A3 | RA1550-A3 | RA1580-A3**  
 HIGH PERFORMANCE VACUUM PUMPS

The DiversiTech International sales team are available to answer your questions or queries on this product. Our experts are waiting for your call +44 (0)115 900 5858 or if you prefer send an email to [sales@diversitech.com](mailto:sales@diversitech.com) or visit [www.diversitech.global](http://www.diversitech.global)

**DIVERSITECH**  
 INTERNATIONAL

Glaisdale Drive East  
 Nottingham NG8 4LY  
 United Kingdom