# ASHP TRUNKING TECHNICAL DATA SHEET

#### DIVERSITECH

INSTAL

# ASHP EXTERNAL 140MM TRUNKING

TR-WC-140 & TR-D-140



TR-WC-140-B & TR-D-140-B

Pipework and insulation running from an air source heat pump should be protected. Our range of trunking comes in a 140mm width with an ivory or black option and accommodates both the insulated flow and return pipework along with any associated cabling.

## **FEATURES**

- · Easy-to install
- · 140mm width accommodates both the insulated flow and return pipe work and other associated cabling
- · Provides a professional and neat finish
- Made from high grade fade resistant PVC
- · Available in ivory and black
- · Protection from the elements, accidental damage and pest damage

Part code IVORY	Description	Depth	Width
TR-D-140	Trunking (2000mm Length)	90mm	140mm
TR-WC-140	Wall Cover	90mm	140mm
TR-CP-140	Straight Connector	90mm	140mm
TR-IC-140	90 Degree Internal Bend	90mm	140mm
TR-FB-140	90 Degree Flat Bend	90mm	140mm
TR-EC-140	90 Degree External Bend	90mm	140mm

Part code BLACK	Description	Depth	Width
TR-D-140-B	Trunking (2000mm Length)	90mm	140mm
TR-WC-140-B	Wall Cover	90mm	140mm
TR-CP-140-B	Straight Connector	90mm	140mm
TR-IC-140-B	90 Degree Internal Bend	90mm	140mm
TR-FB-140-B	90 Degree Flat Bend	90mm	140mm
TR-EC-140-B	90 Degree External Bend	90mm	140mm
TR-EL45-140-B	45 Degree Vertical Bend	90mm	140mm



- Flexi Lite Slab and Foot Kit



### TRUNKING AIR SOURCE HEAT PUMPS

#### EXTERNAL 140MM TRUNKING

The DiversiTech International sales team are available to answer your questions or queries on this product. Our experts are waiting for your call **+44 (0)115 900 5858** or if you prefer send an email to **sales@diversitech.com** or visit **www.diversitech.global** 



Glaisdale Drive East Nottingham NG8 4LY United Kingdom

- ASHP Trunking

